

**NOTES:**

1. THIS CONCEPTUAL DETAIL IS A GUIDE FOR INSTALLATION OF NICHIIHA PRODUCTS. ARCHITECTS/ENGINEERS/CONTRACTORS ARE RESPONSIBLE FOR SUCCESSFUL APPLICATION WHICH DEPENDS UPON SUBSTRATE DESIGN AND CONSTRUCTION BUILT IN ACCORDANCE WITH BEST PRACTICES AND LOCAL BUILDING CODES.
2. FOR THIS APPLICATION ONLY USE NICHIIHA 10', 5/8" PANEL SET VERTICALLY.
3. SHEATHING: 7/16" OR THICKER APA RATED OSB OR PLYWOOD REQUIRED WITH STUD SPACING OTHER THAN 45.5 CM (17-7/8") O.C.
4. METAL FRAMING MEMBERS MUST BE A MINIMUM OF 18 GA.

**TOP OF PANEL  
DETAIL**

FLOOR LINE

FRAMING MEMBER

**STARTER TRACK  
DETAIL**

ULTIMATE CLIP  
(4 CLIPS PER 10' PANEL EDGE)

NICHIIHA PANEL

SHEATHING

WEATHER RESISTANT BARRIER

HORIZONTAL/COMPRESSION  
JOINT DETAIL

FIRST ULTIMATE CLIP JUST ABOVE  
VERTICAL STARTER TRACK

VERTICAL STARTER TRACK  
(FA710T)

FLASHING OPTIONAL

2" ABOVE HARD SURFACE OR  
6" ABOVE FINAL GRADE

**10MM - STANDARD - 10' VERTICAL PANEL - TYPICAL WALL DETAIL**

